

LP 2607 TECHNICAL DATA SHEET

Rigid Foam Polyurethane System

Product Information



LP 2607 is a low-density polyurethane foam designed for processing through plural component dispensing equipment. This material exhibits fast rise and good green strength for applications where fast turnaround is required. The LP 2600 series is designed for a variety of packaging foam applications.

| Physical Properties (Final Product) | Units | Test Method | Results |
|-------------------------------------|-------|---------------|-------------|
| Free Rise Density | pcf | ASTM D1622-03 | 0.70 - 0.85 |
| Compressive Strength | psi | ASTM D1621 | - |
| Tensile Strength | psi | ASTM D-1623 | - |
| Shear Strength | psi | ASTM D-273 | - |
| Elongation | % | ASTM D-412 | - |
| Tear Strength | pli | ASTM D-1004 | - |

| Handling Characteristics | Units | Component A | Component B |
|------------------------------------|---------|-------------|-------------|
| Mix Ratio by Volume | (A/B) | 50 | 50 |
| Mix Ratio by Weight | (A/B) | 53 | 47 |
| Specific Gravity @ 75°F | g/mL | 1.22 - 1.23 | 1.05 - 1.06 |
| Viscocity @ 75°F | cPs | 160 - 220 | 500 - 600 |
| Color | - | Amber | Beige |
| Recommended Processing Temperature | °F | 130 - 140 | 140 - 150 |
| Cream Time @ 75°F | Seconds | 10 - 20 | |
| Gel Time @ 75°F | Seconds | 50 - 60 | |
| Rise Time | Seconds | 60 - 80 | |
| Tack Free Time | Seconds | 75 - 85 | |
| Demold Time | Minutes | 3 - 5 | |
| Final Cure Time | Hours | 1 | |

Properties are typical and not for specifications

Storage and Shelf Life

Components should be kept well sealed in a dry place from 55 to 90°F. Shelf life of unopened containers is six (6) months from manufacturing date. Mix Component B well prior to each use. Purge opened containers with dry nitrogen before resealing. Refer to product SDS for more information.

Packaging

| Component A: | 55 gallon steel drum (closed top) | 500 lb Net Weight |
|--------------|-----------------------------------|--------------------|
| | 275 gallon plastic totes | 2500 lb Net Weight |
| Component B: | 55 gallon steel drum (open top) | 450 lb Net Weight |
| | 275 gallon plastic totes | 2250 lb Net Weight |

For more information contact Eteco, Inc. (714) 480-1370 | info@etecoinc.com www.etecoinc.com

Non-Warranty: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of Eteco, Inc. The data on these sheets relates only to the specific material designated herein. Eteco, Inc. assumes no legal responsibility for use or reliance upon this data. The user should conduct sufficient investigation to establish the suitability of any product for its intended use.